

MATERIAL SAFETY DATA SHEET

No. 1/2

Revised Date : JUL. 8, 2011

Product Name : ACTIVATED CARBON 「GW-H20×40」

Section I

Manufacturer's name : CENAPRO CHEMICAL CORPORATION
Address : Jagobiao Mandaue City Cebu
Philippines
Telephone No. : (63-32) 344-0989
Chemical Name and Synonyms : Activated Carbon
Formula : C

Section II - Hazardous Ingredients

Ingredients : Carbon
CAS No. : 7440-44-0
UN No. : Non-corresponding-matter
Percent : Carbon above 94 %
Ash : less than 3 % including SiO₂ as the main
components.
water : less than 3 %
TLV (ACGIH) : N/A
GHS classification : Do not fall under a classification standard.

Section III - Physical Data

Boiling point (°C) : N/A
Vapor pressure (mmHg) : N/A
Vapor density (Air=1) : N/A
Solubility in water : Insoluble
Specific gravity (H₂O=1) : 1.8 - 2.1
Percent volatile by volume (%) : N/A
Appearance and Odor : Black particulate solid

Section IV - Fire and Explosion Hazard Data

Flash point : N/A
Extinguishing Media : Foam, Multipurpose Dry Chemical and water Type
Extinguishers.
Special Fire Fighting Procedure : None
Unusual Fire and Explosion Hazards : Contact with Strong oxidizers such as Ozone, Liquid
Oxygen, Permanganate, etc. may result in fire.
Auto-Ignition Point (°C) : Above 250°C.

Section V - Healty Hazard Data

Suggested First Aid
Eye Contact : Flush with plenty of water for at least 15 minutes
and medical care immediately.
Skin Contact : Wash with soap and large quantities of water.
Inhalation : Keep the fresh air and warm condition and emergency
care. In case of cyanosis, immediate artificial
breathing. When inhale the dust of Activated Carbon,
rinse mouth with water.

If Swallowed	:Vomit immediately and wash out the mouth completely, Emergency medical care should be required.
Effect of Overexposure	:Avoid exposure to dust levels above 2.9 mg per cubic meter. Long-term and low-level exposure to the dust may bring about the pneumoconiosis.

Section VI - Reactivity Data

Stability	:Stable
Incompatibility (Materials to Avoid)	:Strong Oxidizers such as Ozone, Liquid Oxygen, Permanganate, Nitric Acid etc.
Hazardous Polymerization Conditions to Avoid	:May not occur.
Hazardous Decomposition Products	:Wet activated carbon removes oxygen from air causing a severe hazard to workers inside carbon vessels and enclosed or confined spaces.
	:Contact with strong inorganic acids such as Nitric Acid and Sulfuric Acid may generate hazardous gases such as NO ₂ and SO ₂ .

Section VII - Environmental Information

Spill resource	:Sweeping or Vacuuming (Spills can create nuisance dust and house keeping problems.)
Recommended disposal	:Activated carbons that have adsorbed organic liquids and gases may lower the ignition point and must be checked for ignition point before disposal. Disposal of in accordance with local, state, and federal regulation. Pay special attention not to flow out to the river, water supply system, sewerage, sea. If possible, regeneration is recommended.

Section VIII - Handling and Storage

Protective gloves	:Rubber gloves recommended
Eye protection	:Goggles recommended
Respiratory protection	:NIOSH Approved particular filter respirator is recommended if excessive dust is generated.
Ventilation	:Local exhaust is recommended,
Storage precaution	:Packaged activated carbon is not resistant to weather or outside storage and requires indoor storage facilities.

Concluded